

Engineering Plastics Solutions for Food & Dairy Production

Metal Detectable Engineering Plastics

You inspire ... we materialize®



QUADRANT

Metal Detectable Engineering Plastics



Trends

The foremost goal in the food and beverage production & packaging industry is to deliver high quality, healthy and safe products. A highly regulated market where not meeting international standards can quickly become a major threat to the business, a product recall could turn into the worst case scenario for a producer. At the same time, market dynamics force a continuous cost and productivity improvement.

Producers need to prevent contamination of food caused by e.g. breakage or wear of equipment parts, using predominantly metal detectors. Replacing equipment parts with engineering plastics can improve production speed or extend productive cycles of machines due to reduced downtime significantly.

The growing demand for polymer materials as a replacement of metal parts presents strong demand for new and improved, metal detectable plastics.

Quadrant Answers

Quadrant developed a range of traceable polymer materials, which offer superior properties compared to metal or existing plastics. The manufacturer will be able to choose from a range of products based on the application and the most critical material quality.

Key material qualities:

- Improved impact resistance resulting in less breakage of highly stressed plastic parts in production and process equipment
- Material additives allow detection of very small (27 mm³ and bigger) particles via metal detectors addressing the remaining risk of occurring breakage or wear

Key Benefits

- Improved safety supported by according to FDA and EU standards food contact compliant and metal detectable plastic materials
- Reduced contamination of food, resulting in less related costs and reduced financial and image risk
- Longer productive periods and lower maintenance costs

Quadrant Metal Detectable (MD) Engineering Plastics

Acetron® MD – POM – Blue

- Good balance of stiffness and impact strength for applications where higher dimensional stability is required
- Metal and visual detection by blue colour
- Detection by x-ray also possible
- Continuous use temperature up to 105 °C (221 °F)

Applications:

- Scrapers
- Funnels
- Guiders
- Grippers
- Gears

Current Size Offering:

- Extruded rods
Ø 30/50/80 mm x 1000/3000 mm
- Extruded plates
20/40/80 x 610 x 1000/3000 mm



Acetron® MD Rod



Gears

Nylatron® MD – PA 6 – Dark Blue


- High wear and fatigue resistance
- Lower moisture absorption than standard PA 6
- Metal and visual detection by blue colour
- Detection by x-ray also possible
- Continuous use temperature up to 85 °C (185 °F)

Applications:

- Thrust washers
- Seals
- Rolls

Current Size Offering:

- Extruded rods
Ø 30/50/80 mm x 1000/3000 mm
- Extruded plates
20/40/80 x 610 x 1000/3000 mm



Nylatron® MD Rod/Discs



Seals

TIVAR® MD – PE-UHMW – Dark Grey

- Lower cost material solution for applications with the need for high impact resistance
- Medium dimensional stability due to extreme low water absorption, but high Coefficient of Linear Thermal Expansion (CLTE)
- Good performance in cryogenic environment
- Excellent release properties
- No detection by x-ray

Applications:

- Chain guider elements
- Funnels
- Rolls
- Bushings

Current size offering:

- Extruded rods
Ø 25/50/80 mm x 1000/3000 mm
- Compression molded plates
25/40/80 x 1220 x 3000 mm



TIVAR® Plates/Rod



Funnels for sausage filling

Quadrant Metal Detectable (MD) Engineering Plastics

Ketron® MD PEEK – PEEK – Dark Grey

- Used in applications where high line speeds require good wear resistance or where operating temperatures in use are higher than 130 °C (266 °F)
- For multiple sterilizable machine parts, mainly in equipment with CIP (cleaning in place) or SIP (sterilisation in place)
- Suitable for food approved parts requiring high stiffness without reinforcements
- High dimensional stability for high precision parts
- Good impact/stiffness ratio

Applications:

- Filling pistons
- Manifolds
- Valves
- Scrapers in cookers and high temperature mixers
- Hot oil applications in fryers and ovens
- Thrust washers
- Guiders
- Bushings




Ketron® MD PEEK



Bearing


The material will be produced on demand. Please contact us with your enquiry.

MD Products Performance Comparison



Results based on Quadrant internal tests

Quadrant MD Products Wear Resistance Comparison



Industries

Food Processing

- Meat processing
- Dairy production
- Cheese processing
- Pasta/dough processing
- Sweets processing
- Filling/bottling

Food Packaging

- Applications in direct contact with foodstuff

Quadrant Material Solutions for the Food Industry

Manufacturers constantly need to look for ways to increase production speed. Quadrant's broad range of high performance proprietary machinable plastics meet that challenge whether it's the dimensional stability for increased wear, eliminating costly lubrication or withstanding increased temperatures and more aggressive chemical environments. Following an overview of our material portfolio for the food industry.

Values based on «Temperature of deflection under load» (ISO 75 / Method A: 1,8 Mpa)*

< 80 °C (< 176 °F)	80–120 °C (176–248 °F)	120–160 °C (248–320 °F)	> 160 °C (> 320 °F)
TIVAR® Oil Filled (PE-UHMW + oil)	Ertalon® 6 SA (PA 6)	Techtron® HPV PPS (PPS + solid lubricant)	Quadrant® PSU 1000 (PSU)
TIVAR® SurfaceProtect (PE-UHMW + other additives)	Ertalyte® TX (PET + solid lubricant)	Quadrant® PC 1000 (PC)	Duratron® U1000 PEI (PEI)
TIVAR® 1000 (PE-UHMW)	Nylatron® LFG (PA 6 + oil)	Ketron® PEEK-TX (PEEK + solid lubricant)	Quadrant® PPSU (PPSU)
TIVAR® Ceram P (PE-UHMW + glass beads + additives)	Ertalon® 6 PLA (PA 6)	Ketron® PEEK 1000 (PEEK)	
TIVAR® CleanStat (PE-UHMW + specific additives)	Ertalyte® (PET)	Ketron® MD PEEK (PEEK + additives)	
TIVAR® H.O.T. (PE-UHMW + specific additives)	Ertalon® 66 SA (PA 66)		
TIVAR® MD (PE-UHMW)	Ertacetal® C (POM-C)		
	Fluorosint® 207 (PTFE + mica)		
	Symalit® PVDF 1000 (PVDF)		
	Ertacetal® H (POM-H)		
	Acetron® MD (POM) Nylatron® MD (PA 6)		

* Engineering Note:

A material's heat resistance is broadly characterized by both its «temperature of deflection under load» and its «max. continuously allowable service temperature». The «temperature of deflection under load», formerly called «Heat Deflection Temperature (HDT)», is related to a certain level of stiffness at elevated temperature and it is often considered as the max. temperature limit for moderately to highly stressed, unconstrained components. The «maximum continuous use temperature» on the other hand is related to a certain level of permanent physical property degradation which occurs after long term exposure to elevated temperature (thermal-oxidative degradation).

Material Recommendations for Various Applications

Applications	Products	Applications	Products
Seals	Fluorosint® 207	Gears	Nylatron® LFG
Separation Disc	Ertacetal® C	Bushings	Ertalyte® TX
Stripper	TIVAR® 1000	Needle Guides	Ertacetal® C
Guide for Cutter	TIVAR® 1000	Holding Blocks	TIVAR® 1000
Grinder Bushing	Ertalyte® TX	Chain Blocks	Ertacetal® C
Trust Washers	Ertalyte® TX	Chain Guides	TIVAR® 1000
Cams	Ertalyte® TX	Wear Strips	TIVAR® 1000
Forming Plates	Ertacetal® C	Mixing Paddles	Ketron® 1000 PEEK

Quadrant Engineering Plastic Products Worldwide

Europe

Quadrant EPP AG
Hardstrasse 5
CH-5600 Lenzburg
Tel +41 (0) 62 885 81 50
Fax +41 (0) 62 885 83 85
E-mail: contact@qplas.com

North America

Quadrant EPP USA, Inc.
2120 Fairmont Avenue
PO Box 14235 - Reading, PA 19612-4235
Tel 800 366 0300 / +1 610 320 6600
Fax 800 366 0301 / +1 610 320 6868
E-mail: americas.epp@qplas.com

Asia-Pacific

Quadrant EPP Asia Pacific Ltd
60 Ha Mei San Tsuen, Ping Shan
Yuen Long - N.T. Hong Kong
Tel +852 (0) 24702683
Fax +852 (0) 24789966
E-mail: asia.epp@qplas.com

Belgium | China | France | Germany | Hong Kong | Hungary | India | Italy | Japan | Korea | Mexico
Poland | South Africa | Switzerland | The Netherlands | United Kingdom | United States of America

This brochure and any data and specifications presented here or on our website shall provide promotional and general information about the Engineering Plastic Products (the «Products») manufactured and offered by Quadrant Engineering Plastic Products («Quadrant») and shall serve as a preliminary guide. All data and descriptions relating to the Products are of a general informational nature only. Neither this brochure nor any data and specifications presented on our website shall create or be implied to create any legal or contractual obligation. This brochure and any data or specifications herein do not create expressly or by implication any legal, contractual or warranty obligation whatsoever. No warranty of any kind, either express or implied, is made as to the information contained in these pages, including, but not limited to, all warranties provided for by Louisiana law, any implied warranty of merchantability, of fitness for a particular purpose, and any warranty against hidden defects or redhibitory defects or vices. No information in this brochure creates any express or implied warranty that the goods described herein shall conform to any description herein. Quadrant sells the products described herein solely to sophisticated users and not to consumers, and Quadrant assumes no responsibility that any goods described herein will be fit for any particular purpose for which a Quadrant customer may determine to purchase such goods, except and to the sole extent otherwise provided in a separate written contract.

Any illustration of the possible fields of application of the Products shall merely demonstrate the potential of these Products, but any such description does not constitute any kind of covenant or warranty whatsoever. Irrespective of any tests that Quadrant may have carried out with respect to any Product, Quadrant does not possess expertise in evaluating the suitability of its materials or Products for use in specific applications or products manufactured or offered by the customer respectively. It thus remains the customer's sole responsibility to test and assess the suitability and compatibility of Quadrant's Products for its intended applications, processes and uses, and to choose those Products that according to its assessment meet the requirements applicable to the specific use of the finished product. The customer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, or any consequence thereof, and shall verify its quality and other properties.

Acetron®, Duratron®, Ertalon®, Ertalyte®, Ertacetal®, Fluorosint®, Ketron®, Nylatron®, Symalit®, Techtron® and TIVAR® are registered trademarks of the Quadrant group of companies.

Learn More Online at www.quadrantplastics.com

Quadrant has extensive product and machining information available online. Our website is a portal to a wealth of technical data and the easiest way to contact our application specialists. Our team stands ready to help offer solutions to your toughest problems.

Distributed by: